



SEU and Test Considerations for FPGA Devices

Melanie Berg
Muniz Technologies Incorporated
NASA/GSFC Radiation Effects an
Analysis Group

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens
Greece, September 27-29, 2006.

Page 1

Outline



- **Field Programmable Gate Array (FPGA) Background**
 - Definition
 - Implementations in space missions
 - Available Technologies
- **Single Event Upsets (SEUs) and Single Event Transients (SETs)**
 - Definition
 - How they Effect FPGAs
- **Testing**
 - Goals
 - Considerations
 - Data Analysis
- **Summary**

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece,
September 27-29, 2006.

Page 2

What's the Issue?



Faulty Chips Delay Launch of Japanese Imaging Satellite

PAUL KALLENDER-UMEZU, TOKYO
MISSY FREDERICK, WASHINGTON

The Japanese government has decided to postpone the launch of the nation's next reconnaissance satellite by six months or more following the discovery of potentially defective integrated circuits in the satellite, a government official said August 26.

The Prime Minister's Cabinet Office, which is in charge of the nation's Information Gathering Satellite (IGS) program, decided Aug. 25 to postpone the launch of what would be the nation's third reconnaissance satellite in orbit after deciding it was necessary to replace a number of field-programmable gate arrays (FPGAs) made by Actel Corp. of Mountain View, Calif., according

to Yasuhiro Itakura, research officer at Japan's Cabinet Satellite Intelligence Center, which is part of the Cabinet Office.

The satellite, which carries an optical sensor, was to have been launched by a Japanese H-2A rocket from the Tanegashima Launch Center before the end of March 2006, but it will take about six months to replace the potentially faulty chips and test the satellite to prepare it for flight, Itakura said in an August 26 telephone interview.

Some 10 chips need to be replaced, he said. Details about when the problem was discovered were not available at the time of the interview.

Problems with Actel's earlier version of FPGAs were discovered in autumn 2003, after more than 1 million of the devices were

shipped to various vendors.

Ken O'Neill, director of military and aerospace product marketing for Actel, said after news of the defect became known, Actel supplied the Japanese government with the latest version of the company's FPGAs which the company has the option to install in place of the old version. Since then, the government has been doing reliability testing of both the old and new product, though Actel had not received official word that the company was

reliability of the earlier version is high, but the latest version of the software does offer a higher level of reliability," he said.

FPGAs contain hundreds of thousands of programmable elements, according to O'Neill, and the defect found in the old version of the chips affected one attribute within the design, causing it to fail. O'Neill said the chips that do fail usually do so early in the lifetime of the part.

As a supplier, Actel

tered, Itakura said.

Each of the next information-gathering satellites to be launched will have the same capabilities as the original satellites launched by an H-2A rocket in March 2003. One type of satellite has an optical sensor capable of 1-meter resolution, while the radar-type satellite has a resolution of 1-3 meters.



The IGS program was developed in response to an August 1998 incident when North Korea launched a missile that overflew U.S. territory and landed in the sea. Two more satellites are planned to join the first pair in November 2003, but the first two satellites were destroyed by an H-2A rocket carrying

Comments: info@nasa.gov

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 3


Field Programmable Gate Arrays (FPGA)



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 4


General FPGA Architecture



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 5

Role of FPGA/ASIC Devices within Space Missions




To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 6

Configuration: Key Difference in FPGA Technologies



- Configuration defines: Functionality and Connectivity
- Configuration is programmable



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 7

Single Event Upsets (SEUs) and Single Event Transients (SETs)




To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 8

Single Event Upsets (SEU) and Single Event Transients (SET)




- CMOS transistors have become more susceptible to incurring faults.
- Why?
 - reduction in core voltage
 - decrease in transistor geometry
 - increase in switching speeds,
- A Fault Occurs when a transistor that is turned off:
 - Collects Charge at the drain
 - turns on with enough charge to change the state of the output



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 9

Transient Generation and Propagation



Add something about set capture in dff


ge 10



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 11


Example 1: Xilinx and the Complexity of a Configuration Logic Block (CLB)



To be presented by Melanie Berg at Radiation and its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 12

Example: Susceptibility in a Xilinx 4-Input Look Up Table (LUT)



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 13

Example 1: Summary....How Do SET's/SEU's Effect Xilinx FPGAs?



- Configuration Memory hit:
 - Largest area of concern for the Device
 - The entire FPGA can become un-configured.
- Logic/Connector Hit
 - *Frequency dependency*: SETs can be caught by Flip-Flops
 - *Frequency independent*: SEU can occur in Flip-Flop
- Single Event Functional Interrupt (SEFI): Hits to
 - Power On Reset
 - Configuration Control logic
- What considerations must be taken to test for these conditions?

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 14



Testing Complex FPGA Implementations Targeted for Critical Missions

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece,
September 27-29, 2006.

Page 15



Choosing the Most Cost Effective FPGA for a Project with Critical Requirements

- Define realistic Requirements
- Trade-offs:
 - Reliability
 - Performance
 - Schedule
 - Total Cost
- Define a methodology for trade-off analysis
- Radiation Testing is key and can be broken into 2 major categories:
 - Characterization:
 - General device study
 - Simple Test structures
 - Qualification
 - Project specifics
 - Test structures may be more complex

We'll Focus on Device Characterization

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece,
September 27-29, 2006.

Page 16

Goals for Device Characterization



- How radiation-tolerant (in general) is the Device Under Test (DUT)?
- Test for:
 - Clock Tree Susceptibility
 - Rest Tree Susceptibility
 - Sequential logic Hardness
 - Combinatorial Error Cross-Section Contribution
 - I/O Susceptibility
 - Single Event Functional Interrupts (SEFI)
 - Configuration Memory Susceptibility (**SRAM –Based Only**)

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 17

DUT Radiation Test Strategies



- Push the limits of the DUT.
 - Timing variations (very slow to fastest clock rates)
 - Types of logic cells (check device technology library)
 - Fill Device with logic
 - Safe I/O strategies
- Designs should be simple so that faults are not masked and undecipherable.
- Designs should represent realistic implementations
 - Proper reset structures
 - Synchronous design techniques
 - Various levels of combinatorial logic between DFF structures
 - Fanout variation

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 18

Common DUT Characterization Test Structures




- Shift Register Strings (sequential logic)
- Combinatorial Clouds of logic between (sequential cells)
- Large quantities of I/O to accommodate data variation, system clock rate variation, design interfacing, and I/O susceptibility testing

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 19

Testing Sequential and Combinatorial logic



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 20

Tester Radiation Test Strategies




- Attention to Timing Characteristics of the DUT
- Application of corner case input variations (stress the part)
- Deterministic DUT Data Capture
- Tester to DUT Interface Limitations
 - Number of I/O
 - Simultaneously Switching Outputs (SSO)
 - Interface connector speed

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 21

NASA GSFC Low Cost Digital Tester



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 22

Analyzing Test Data – Asking the Right Questions



- Does the device stay configured?
- Is the DUT schematic supplied?
- Is the DUT implementation a reliable design?
 - Synchronous design techniques
 - “Single Integrity” solution applied
- How reliable is the supplied inputs and data capture scheme of the tester?
- What are the maximum and minimum frequencies supplied to the DUT during test and how do they relate to the timing specifications of the device?
- What are the data rates? (May be difficult to determine for complex designs)
- Are there SEFIs
- Is there speed degradation?

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 23

Data Analysis Example



- Actel Corporation and NASA-GSFC collaborated in supplying SEU RTAX-S device specific data
- Data was supplied at 2MHz testing frequency
- Simple shift register test structures were implemented
- Question: Was the supplied data an Efficient characterization of the devices?

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.


Page 24

Actel Logic Blocks: Sequential and Combinatorial




■ RCELL (Sequential):

- Triple Mode Redundant (TMR) Mitigation
- Inputs are shared (single points of failure)
- contains more logic (not shown)
 - 2 MUXs one for logic and one for clocking
 - Adds more sources of failure



■ CCELL (Combinatorial):

- Logic Block is generally a MUX structure
- Addition of block should increase error cross section as frequency increases



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 25

Actel Expectations: SET Frequency Response



- In general ... Combinatorial.....
- RCELL contains some
- CCELL should make a considerable contribution due to frequ dep

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 26

Data Analysis Example (Continued)




- Another effort between Actel and NASA-GSFC was undertaken
- Clock Rates were supplied to the DUT from 15MHz to 150MHz
- DUT Input Data:
 - Alternating data was supplied at half the clock rate
 - Static "0"
 - Static "1"
- Several Designs were implemented to analyze the potential increased susceptibility to transients when utilizing C-CELLS
- Synchronous Design Approach was implemented in the DUT and in the tester.

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 27

RTAX-S Data: Earlier and Current Test Data



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 28

Survey – Why Was the Original 2MHz Data Acceptable?



- Asked Engineers and Physicists.
- Here's the Best of:

Engineers:

- Told Frequency dependency does not exist
- Was not aware of transients and their effects in circuitry


Physicists:

- Based on the new 150MHz, the original assumption that the data is scalable holds true – (2Mhz to 150Mhz testing should result in about 2 orders of magnitude between data sets

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.


Page 29

2 Orders of Magnitude is True in this Case



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 30



Comparison of FPGA Radiation Test Data (Dynamic Shift Register Tests Only)			
	Actel	Aeroflex	Xilinx
Mitigation	TMR: embedded in device	DICE: embedded in device	Scrubbing: (overwriting Configuration Memory) Can not test without
Frequency	150 MHz	120 MHz	50 MHz
Frequency Dependent	Yes	No	?
Data Dependant	Yes	Yes	?
Lowest Cross Sections	✓		
Stay configured	Yes	Yes	No
SEFI	No	No	Yes
Speed Degradation	No	Yes – Too much exposure to high LET	No

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 32

Data Analysis Conclusion



- We are aware of possible faults within circuitry
- When analyzing data, the proper precautions must be taken and the correct questions must be asked?

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 33

Summary



- FPGAs have proven to be cost effective solutions to large, complex systems
- Configuration and logic structures vary among manufacturers
- When considering potential SEUs and deciding which device is best suited for a project, special attention must be taken concerning
 - Configuration Hardness
 - Logic Level Hardness
 - Ease of system level implementation
 - Function necessities (speed, data manipulation, ...)
 - Mitigation schemes (if necessary)

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 34


Summary (Continued...)



- Radiation Testing is necessary to characterize device level SEU data.
- Care must be taken to implement appropriate tests in order to push the DUT to its limits
 - Speed
 - Reliable data supply and capture
 - Realistic DUT design implementation
 - Simplistic structures – avoid fault masking
- While analyzing data the proper questions should be asked to ensure the data efficiently characterizes the device.

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 35




SEU and Test Considerations for FPGA Devices


Melanie Berg
 Muniz Technologies Incorporated
 NASA/GSFC Radiation Effects and Analysis Group

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 1




Field Programmable Gate Arrays (FPGA)



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 4




Outline


- Field Programmable Gate Array (FPGA) Background
 - Definition
 - Implementations in space missions
 - Available Technologies
- Single Event Upsets (SEUs) and Single Event Transients (SETs)
 - Definition
 - How they Effect FGAs
- Testing
 - Goals
 - Considerations
 - Data Analysis
- Summary

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 2



General FPGA Architecture



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 5



What's the Issue?

Faulty Chips Delay Launch of Japanese Imaging Satellite

PAUL DALLINGER, SPACE, SPACE RESEARCH, WASHINGTON

The Japanese government has decided to postpone the launch of the nation's next reconnaissance satellite by six months or more following the discovery of potentially defective integrated circuits in the satellite, a space news official said August 28.

The Prime Minister's Cabinet Office, which is in charge of the nation's Information Gathering Satellite (IGS) program, decided Aug. 28 to postpone the launch of what would be the nation's third reconnaissance satellite to orbit after deciding it was necessary to replace a number of field-programmable gate arrays (FPGAs) chips made by Intel Corp. of Menlo Park, Calif., according to Yoshio Ishihara, research officer at Japan's Cabinet Office Intelligence Center which is part of the Cabinet Office.

The satellite, which carries an optical sensor, was to have been launched by a Japanese H-IIA rocket from the Tanegashima Launch Center before the end of March 2006, but it will take about six weeks to replace the potentially faulty chips and test the satellite to prepare for flight, Ishihara said in an August 28 telephone interview.

Some 10 chips need to be replaced, he said. Details about when the problem was discovered were not available at the time of the interview.

Problems with Intel's earlier versions of the FPGAs were discovered in summer 2005, after about 1 million of the devices were shipped to various vendors.

Ken O'Neill, director of military and aerospace product marketing for Intel, said after some of the defect became known, Intel supplied the Japanese government with the newer version of the component.

Intel had the option to recall its chips, but the company chose to recall its place of the old version. Since then, the government has been doing reliability testing of both the old and new products, though Intel had not received official word that the chips were faulty.

The reliability of the earlier version is high, but the latest version of the software does offer a higher level of reliability, he said.


Intel has been testing the new version of the software for several months, according to O'Neill, and the defect found in the old version of the chips affected one or two chips within the design, testing it to fail, O'Neill said. The chips do not usually do so early in the lifetime of the part.

In a separate report, a problem with the satellite's software was discovered. Two more satellites planned for launch in September 2006, but they were not affected.


The H-IIA rocket carrying 11-25 satellites carrying

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 3



Role of FPGA/ASIC Devices within Space Missions



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 6

Configuration: Key Difference in FPGA Technologies

- Configuration defines: Functionality and Connectivity
- Configuration is programmable

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006. Page 7

Transient Generation and Propagation

Add something about set capture in dff

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006. Page 10

Single Event Upsets (SEUs) and Single Event Transients (SETs)

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006. Page 8

How do SEUs and SETs Effect FPGAs?

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006. Page 11

Single Event Upsets (SEU) and Single Event Transients (SET)


- CMOS transistors have become more susceptible to incurring faults.
- Why?
 - reduction in core voltage
 - decrease in transistor geometry
 - increase in switching speeds,
- A Fault Occurs when a transistor that is turned off:
 - Collects Charge at the drain
 - turns on with enough charge to change the state of the output

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006. Page 9

Example 1: Xilinx and the Complexity of a Configuration Logic Block (CLB)

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006. Page 12

Example: Susceptibility in a Xilinx 4-Input Look Up Table (LUT)



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 13

Choosing the Most Cost Effective FPGA for a Project with Critical Requirements

- Define realistic Requirements
- Trade-offs:
 - Reliability
 - Performance
 - Schedule
 - Total Cost
- Define a methodology for trade-off analysis
- Radiation Testing is key and can be broken into 2 major categories:
 - Characterization:
 - General device study
 - Simple Test structures
 - Qualification
 - Project specific
 - Test structures may be more complex

We'll Focus on Device Characterization

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 16

Example 1: Summary....How Do SET's/SEU's Effect Xilinx FPGAs?

- Configuration Memory hit:
 - Largest area of concern for the Device
 - The entire FPGA can become un-configured.
- Logic/Connector Hit
 - Frequency dependent: SETs can be caught by Flip-Flops
 - Frequency independent: SEU can occur in Flip-Flop
- Single Event Functional Interrupt (SEFI): Hits to
 - Power On Reset
 - Configuration Control logic
- What considerations must be taken to test for these conditions?

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 14

Goals for Device Characterization

- How radiation-tolerant (in general) is the Device Under Test (DUT)?
- Test for:
 - Clock Tree Susceptibility
 - Rest Tree Susceptibility
 - Sequential logic Hardness
 - Combinatorial Error Cross-Section Contribution
 - I/O Susceptibility
 - Single Event Functional Interrupts (SEFI)
 - Configuration Memory Susceptibility (SRAM –Based Only)

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 17

Testing Complex FPGA Implementations Targeted for Critical Missions

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 15

DUT Radiation Test Strategies

- Push the limits of the DUT.
 - Timing variations (very slow to fastest clock rates)
 - Types of logic cells (check device technology library)
 - Fill Device with logic
 - Safe I/O strategies
- Designs should be simple so that faults are not masked and undecipherable.
- Designs should represent realistic implementations
 - Proper reset structures
 - Synchronous design techniques
 - Various levels of combinatorial logic between DFF structures
 - Fanout variation

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 18


Common DUT Characterization Test Structures

- Shift Register Strings (sequential logic)
- Combinatorial Clouds of logic between (sequential cells)
- Large quantities of I/O to accommodate data variation, system clock rate variation, design interfacing, and I/O susceptibility testing

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 19


NASA GSFC Low Cost Digital Tester



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 22

Testing Sequential and Combinatorial logic



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 20

Analyzing Test Data – Asking the Right Questions

- Does the device stay configured?
- Is the DUT schematic supplied?
- Is the DUT implementation a reliable design?
 - Synchronous design techniques
 - “Single Integrity” solution applied
- How reliable is the supplied inputs and data capture scheme of the tester?
- What are the maximum and minimum frequencies supplied to the DUT during test and how do they relate to the timing specifications of the device?
- What are the data rates? (May be difficult to determine for complex designs)
- Are there SEFIs
- Is there speed degradation?

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 23

Tester Radiation Test Strategies

- Attention to Timing Characteristics of the DUT
- Application of corner case input variations (stress the part)
- Deterministic DUT Data Capture
- Tester to DUT Interface Limitations
 - Number of I/O
 - Simultaneously Switching Outputs (SSO)
 - Interface connector speed

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 21

Data Analysis Example


- Actel Corporation and NASA-GSFC collaborated in supplying SEU RTAX-S device specific data
- Data was supplied at 2MHz testing frequency
- Simple shift register test structures were implemented
- Question: Was the supplied data an Efficient characterization of the devices?

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 24

Actel Logic Blocks: Sequential and Combinatorial


- RCELL (Sequential):
 - Triple Mode Redundant (TMR) Mitigation
 - Inputs are shared (single points of failure)
 - contains more logic (not shown)
 - 2 MUXs one for logic and one for clocking
 - Adds more sources of failure
- CCELL (Combinatorial):
 - Logic Block is generally a MUX structure
 - Addition of block should increase error cross section as frequency increases



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 25

RTAX-S Data: Earlier and Current Test Data



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 28

Actel Expectations: SET Frequency Response

- In general ...Combinatorial.....
- RCELL contains some
- CCELL should make a considerable contribution due to frequency

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 26

Survey – Why Was the Original 2MHz Data Acceptable?

- Asked Engineers and Physicists.
- Here's the Best of:

Engineers:

- Told Frequency dependency does not exist
- Was not aware of transients and their effects in circuitry

Physicists:

- Based on the new 150MHz, the original assumption that the data is scalable holds true – (2MHz to 150MHz testing should result in about 2 orders of magnitude between data sets)

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 29


Data Analysis Example (Continued)

- Another effort between Actel and NASA-GSFC was undertaken
- Clock Rates were supplied to the DUT from 15MHz to 150MHz
- DUT Input Data:
 - Alternating data was supplied at half the clock rate
 - Static "0"
 - Static "1"
- Several Designs were implemented to analyze the potential increased susceptibility to transients when utilizing C-CELLS
- Synchronous Design Approach was implemented in the DUT and in the tester.

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.


Page 27

2 Orders of Magnitude is True in this Case



To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006.

Page 30



NASA

Summary

- FPGAs have proven to be cost effective solutions to large, complex systems
- Configuration and logic structures vary among manufacturers
- When considering potential SEUs and deciding which device is best suited for a project, special attention must be taken concerning
 - Configuration Hardness
 - Logic Level Hardness
 - Ease of system level implementation
 - Function necessities (speed, data manipulation, ...)
 - Mitigation schemes (if necessary)

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006. Page 34

NASA

Comparison of FPGA Radiation Test Data (Dynamic Shift Register Tests Only)

	Actel	Aeroflex	Xilinx
Mitigation	TMR: embedded in device	DICE: embedded in device	Scrubbing: (overwriting Configuration Memory) Can not test without
Frequency	150 MHz	120 MHz	50 MHz
Frequency Dependent	Yes	No	?
Data Dependent	Yes	Yes	?
Lowest Cross Sections	✓		
Stay configured	Yes	Yes	No
SEFI	No	No	Yes
Speed Degradation	No	Yes – Too much exposure to high LET	No

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006. Page 32

NASA

Summary (Continued...)

- Radiation Testing is necessary to characterize device level SEU data.
- Care must be taken to implement appropriate tests in order to push the DUT to its limits
 - Speed
 - Reliable data supply and capture
 - Realistic DUT design implementation
 - Simplistic structures – avoid fault masking
- While analyzing data the proper questions should be asked to ensure the data efficiently characterizes the device.

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006. Page 35

NASA

Data Analysis Conclusion

- We are aware of possible faults within circuitry
- When analyzing data, the proper precautions must be taken and the correct questions must be asked?

To be presented by Melanie Berg at Radiation and Its Effects on Components and Systems (RADECS) 2006, Athens Greece, September 27-29, 2006. Page 33